## L-Factor Pressure Gauges

GG-531005-TG & GG-531105-TG



## GG-531005-TG

- Pressure Gauge
- 1/4" NPT-Lower Inlet

SPECIFICATIONS	
MAXIMUM PSI:	0-7500 PSI
CONSTRUCTION:	Liquid Filled
SIZE:	2.5" Face
CASE:	304 Stainless Steel
SAFETY FACTOR:	4:1
WETTED PARTS:	Copper Alloy
WINDOW:	Polycarbonate
POINTER:	Black Aluminum
DIAL LAYOUT:	#'s every 1000 PSI Tick marks every 100 PSI
MEDIA TEMP:	140°F Max
AMBIENT TEMP:	-40°F to 140°F

- Intended for adverse service conditions where pulsating or vibration exists (with liquid filling).
- Compressors & Hydraulics
- Suitable for gaseous or liquid media that will not obstruct the pressure system.
- · Vibration & shock resistant (with liquid filling).
- · Weather tight.

## "CRITICAL FACTOR" PROMISE

We put our heart and soul into our products. We invite you to take a step up to L-Factor. Like taking a step back in time when a promise was gold - you'll be satisfied - and that's our promise!

When used in proper application and according to our instructions, L-Factor warrants this product to be free from defects in material and workmanship for a period of 12 months. Refer to the complete warranty information for details. Step up to an L-Factor product.

Old fashioned craftsmanship, new fashioned technology, working together to produce Genuine L-Factor products.



## **GG-531105-TG**

- Pressure Gauge
- 1/4" NPT-Back Inlet



4740 NW 157 Street, Miami Lakes, FL 33014 Phone: (305) 430-0550 Fax: (305) 430-0864 email: L-factor@ix.netcom.com web page: www.lawrence-factor.com